VPX025

6U VPX 28V DC Input Power Module 1100W

VPX025

Key Features

- Power Module for Open VPX VITA 62
- 6U VPX Systems
- 1100W Output Power
- 2KVdc input to output functional isolation)
- Input voltage +16V to +45V (nominal +28V)
- Available in Conduction Cooled
- Meets MIL-STD-704F, MIL-STD-461G, MIL-STD-810G MIL-STD-1275E
- Health Management through dedicated Processor
- Up to four modules for parallel operation and/or redundancy

Benefits

- Most comprehensive VPX products in the market
- Electrical, mechanical, software, and system-level expertise in house
- Full system supply from industry leader
- AS9100 and ISO9001 certified company

OpenVPX™

vadatech
THE POWER OF VISION

VPX025

The VPX025 is a power module per VITA 62. The VPX025 is designed for 6U VPX systems and provides +12V, +5V, -12V_AUX, +12V_AUX and +3.3V_AUX to the backplane. Up to four VPX025 could be utilized for parallel operation and/or redundancy.

The module has dedicated health management per VITA 46.11 and interfaces to the backplane using dual IPMI buses. The module has ENABLE, INHBIT, FAIL, Geographic address, and SYSRESET connections to the backplane.

The module is designed to meet the following MIL-STDs:

- MIL-STD-704F
- MIL-STD-461G
- MIL-STD-810G
- MIL-STD-1275E

The VPX025 can deliver the following power on each rail:

- +12V @ 91A
- +5V @ 80A
- +12V_AUX @ 4A
- -12V @ 1.2A
- +3.3V_AUX @ 10A

Please note that total power of the module cannot exceed 1100W across all the rails.

Figure 1: VPX025 (Conduction-Cooled)

Figure 2: VPX025 Front View (Conduction-Cooled)

Figure 3: VPX025 Alternative View (Conduction-Cooled)

Figure 4: VPX025 Front Panel View (Conduction-Cooled)

info@vadatech.com | www.vadatech.com



Figure 5: Main +12V output. The rest of the powers are generated from the +12V



Figure 6: Main +12V output. The rest of the powers are generated from the +12V

Block Diagram



Figure 7: VPX025 Functional Block Diagram

Specifications

Architecture		
Physical	**Dimensions**	6U, 1” pitch (5 HP panel)
Standards		
VPX	**Type**	VITA 46.0
VPX	**Type**	VITA 65 OpenVPX
Module Management	**IPMI**	IPMI v2.0
Configuration		
Power	**VPX025**	Power Entry Module with +16V to +45V input 1100W
		2KVdc Isolation
Front Panel	**Micro USB**	RS-232 for Health Management
	LEDs	User defined by Health Management
Onboard Interfaces		Dual IPMI Buses
VPX Interfaces	**Slot Profiles**	See Ordering Options
	Rear IO	Per VITA 62 (Fail, Inhibit, Geographic address, etc.)
	Backplane	Connector per VITA 62
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards	
Warranty	Two (2) years, see VadaTech Terms and Conditions	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

Ordering Options

VPX025– 000-000-GHJ

		G = Applicable Slot Profile
		0 = 5 HP, VITA 48.1 1 = Reserved
		H = Environmental
		See Environmental Specification
		J = Conformal Coating
		0 = No coating 1 = Humiseal 1A33 Polyurethane 2 = Humiseal 1B31 Acrylic3 3 = Parylene

Notes:

Environmental Specification

	Air Cooled		Conduction Cooled		
Option H	**H = 0**	**H = 1**	**H = 2**	**H = 3**	**H = 4**
Operating Temperature	AC1* (0°C to +55°C)	AC3* (-40°C to +70°C)	CC1* (0°C to +55°C)	CC3* (-40°C to +70°C)	CC4* (-40°C to +85°C)
Storage Temperature	C1* (-40°C to +85°C)	C3* (-50°C to +100°C)	C1* (-40°C to +85°C)	C3* (-50°C to +100°C)	C3* (-50°C to +100°C)
Operating Vibration	V2* (0.04 g2/Hz max)	V2* (0.04 g2/Hz max)	V3* (0.1 g2/Hz max)	V3* (0.1 g2/Hz max)	V3 (0.1 g2/Hz max)
Storage Vibration	OS1* (20g)	OS1* (20g)	OS2* (40g)	OS2* (40g)	OS2* (40g)
Humidity	95% non-condensing	95% non-condensing	95% non-condensing	95% non-condensing	95% non-condensing

Notes:
*Nomenclature per ANSI/VITA 47. Contact local sales office for conduction cooled (H = 2, 3, 4).

Related Products

VPX021

- Power Module for Open VPX VITA 62
- 3U VPX Systems
- 600W Output Power

VPX029

- Power Module for Open VPX VITA 62
- 3U VPX Systems
- 600W Output Power

VPX028

- Power Module for Open VPX VITA 62
- 6U VPX Systems
- 500W Output Power

Contact

VadaTech Corporate Office

198 N. Gibson Road, Henderson, NV 89014

Phone: +1 702 896-3337 | Fax: +1 702 896-0332

Asia Pacific Sales Office

7 Floor, No. 2, Wenhu Street, Neihu District, Taipei 114, Taiwan

Phone: +886-2-2627-7655 | Fax: +886-2-2627-7792

VadaTech European Sales Office

VadaTech House, Bulls Copse Road, Southampton, SO40 9LR

Phone: +44 2380 016403

info@vadatech.com | www.vadatech.com

Choose VadaTech

We are technology leaders

- First-to-market silicon
- Constant innovation
- Open systems expertise

We commit to our customers

- Partnerships power innovation
- Collaborative approach
- Mutual success

We deliver complexity

- Complete signal chain
- System management
- Configurable solutions

We manufacture in-house

- Agile production
- Accelerated deployment
- AS9100 accredited

vadatech

THE POWER OF VISION

Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

© 2023 VadaTech Incorporated. All rights reserved.

DOC NO. 4FM737-12 REV 01 | VERSION 1.6 – APR/26